

NetWaySP8X

8-port Hardened PoE Switch with Integral Power

Altronix NetWaySP8X PoE+ Indoor Hardened Switch provides two (2) 1Gb SFP (Fiber) ports and eight (8) PoE+ (30W) or two (2) Hi-PoE (60W) ports, passing data for PoE/PoE+/Hi-PoE compliant devices. Cameras/edge devices may be located up to 100m from the unit. Embedded LINQ Technology allows you to monitor, control, and report power and diagnostics from anywhere.




NetWaySP8X

Key Features

- Two (2) Gigabit SFP ports
- 115W total power:
 - Eight (8) PoE/PoE+ (up to 30W) ports or two (2) Hi-PoE (60W) ports
- Two (2) 10/100/1000 Mbps ports
- Six (6) 10/100 Mbps ports
- IEEE 802.3at (30W), IEEE 802.3af (15W) compliant, or Hi-PoE (60W)
- PoE activity LED indicators
- Automatic switch over to stand-by battery when AC fails
- VLAN (Virtual Local Area Networks) subnetwork allows for the grouping together of devices for improved network traffic and higher security
- UL Listed in the U.S. and Canada
- CE European Conformity
- Lifetime Warranty

Similar products

NetWaySP8WPX	Outdoor 8-port PoE+ Hardened Switch in NEMA 4/4X, IP66-11 enclosure which accommodates stand-by batteries
NetWaySP8WP	Outdoor 8-port PoE+ Hardened Switch in NEMA 4/4X, IP66-11 enclosure
NetWaySP8WPN	Outdoor 8-port PoE+ Hardened Switch only in NEMA 4/4X, IP66-11 enclosure
NetWaySP8PL	8-port PoE+ Hardened Switch with Integral Power on a Backplane
NetWaySP8B	8-port PoE+ Hardened Switch (board only)


Lifetime Warranty

NetWaySP8X

8-port Hardened PoE Switch with Integral Power



Typical Application



Lifetime Warranty

Specifications

Input

Voltage 115VAC, 60Hz, 2.5A or 230VAC, 50/60Hz, 1.3A
Fusing 5A/250V

Power Output

Maximum Power Eight (8) PoE+ (30W) ports or two (2) Hi-PoE (60W) ports
IEEE 802.3at (30W) and IEEE 802.3af (15W) compliant
115W total power
Integral surge protection

Fiber Ports: Two (2) Gigabit SFP ports

Ethernet Ports: Six (6) 10/100 Mbps and two (2) 10/100/1000 Mbps ports
Connectivity: RJ45, auto-crossover
Wire type: 4-pair CAT5 or better structured cable
Distance: up to 100m
Speed: 10/100/1000 Mbps, half/full duplex, auto negotiation

Back-up Battery (not included)

Type Sealed lead acid or gel type
Failover Upon AC loss, instantaneous

Indicators (LED)

Individual PoE On LEDs for each port
Individual IP Link status, 10/100Base-T/active LEDs for each port
ALOS LED indicates fiber connection for SFP port
Heartbeat LED indicates proper operation of the unit

VLAN:

Multiple management VLAN assignment
802.1Q Tagged VLAN. Up to 10 VLAN groups. ID Range 2-4095

LINQ Technology:

Remote network management allows for camera/device reset and monitoring
Provides local and/or remote access to critical information via LAN/WAN
Email and Windows Dashboard Alert notifications report real-time diagnostics
Event log tracks history.

Agency Listings

UL/cUL UL60950-1 (Information Technology Equipment)
CE European Conformity

Physical and Environmental

Enclosure Dimensions (H x W x D approx.): 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.6mm)

Product Weight / Shipping (approx.)

Product Weight: 6.65 lb. (3.02 kg)
Shipping Weight: 7.55 lb. (3.42 kg)

Temperature

Operating: 60W: -40°C to 75°C (-40°F to 167°F)
75W: -40°C to 70°C (-40°F to 158°F)
100W: -40°C to 55°C (-40°F to 131°F)
115W: -40°C to 45°C (-40°F to 113°F)

Storage: -40°C to 85°C (-40°F to 185°F).

Relative Humidity: 85% +/-5%

BTU/Hr. (approx.): 61 BTU/Hr.

Operating Altitude: -304.8 to 2,000m

Accessories (order separately)



SFP Modules - Hot pluggable Transceivers

P1MM Multi-Mode SFP Module for distances up to 550m
P1SM10 Single-Mode SFP Module for distances up to 10km
P1AB2K Single Strand SFP Module for distances up to 2km
P1GCE Copper SFP Module for distances up to 100m



NetWaySP1A

Ethernet over Fiber Media Converter/Repeater for applications requiring an additional SFP (Fiber) Port
NetWaySP1A PoE powered media converter/repeater converts 10/100/1000 Mbps to Fiber (1000Base-X/SX/LX).

Lifetime Warranty